- 12. (Amended) A system according to claim 1, whereby said filter is a candle filter or a tubular filter.
- 14. (Amended) The filtration of hot gases in a system according to claim 1 at temperatures higher than 850°C.--

REMARKS

Applicants respectfully request that the foregoing amendments to Claims 4, 5, 7, 9, 10, 12, and 14 be entered in order to avoid this application incurring a surcharge for the presence of one or more multiple dependent claims. A marked-up version of the claims showing the changes made is attached.

Respectfully submitted,

<u>December 18, 2001</u>

Date

Richard L. Schwaab

Registration No. 25,479

Jahward

FOLEY & LARDNER 3000 K Street, N.W. Suite 500 Washington, D.C. 20007-5109 (202) 672-5300

VERSIONS WITH MARKINGS TO SHOW CHANGES MADE

- 4. A system according to claim 1[or 3], whereby the filter medium has a porosity between 60 and 85%.
- 5. A system according to [any one of claims 1 to 4]claim 1, whereby a mesh is fixed to the filter medium as the flow out side, said mesh is made from a Fe-Cr-Al based alloy.
- 7. A system according to [any one of claims 1 to 6]claim 1, whereby the additional element is Y with a concentration between 0.03 and 0.5%.
- 9. A system according to [any one of claims 1 to 6]claim 1, whereby the sum of the additional elements is between 0.01 and 1%.
- 10. A system according to [any one of claims 1 to 9]claim 1, whereby an Al₂O₃ layer is formed on the surface of said filter.
- 12. A system according to [any one of claims 1 to 11] claim 1, whereby said filter is a candle filter or a tubular filter.
- 14. The filtration of hot gases in a system according to [claims 1 to 13]<u>claim 1</u> at temperatures higher than 850°C.